


Data sheet 2MV 520








2MV

Performance curve for Vacuum pump



Performance curve for Compressor



The performance curves are based on air at a temperature of 15 °C and an atmospheric pressure of 1013 mbar with a tolerance of +/- 10 %.

The total pressure differences are valid for suction and ambient temperatures up to 25 °C.

For other conditions please confer with us.

Each 2MV type can be applied both as vacuum pump and compressor in continuous operation over the total stated performance curve range.

Selection and ordering data

Type 2MV520

| Curve No. | Order No. | Frequency Hz | Rated power kW | Input voltage V | Input current A | Permissible total differential pressure ²⁾ Vacuum mbar | Compressor mbar | Sound pressure level ³⁾ dB(A) | Weight ca. kg |
|-----------|-----------|--------------|----------------|-----------------|-----------------|--|-----------------|--|---------------|
|-----------|-----------|--------------|----------------|-----------------|-----------------|--|-----------------|--|---------------|

3~ 50/60 Hz IP55 insulation material class F 1)

| | | | | | | | | | | | |
|-------|-------------|----|-----|--------------------------------|----------------------------|----------------|---------------|--------------|------------|----------|----------|
| A 240 | 2MV 520-H46 | 50 | 3.0 | 200D ... 240D 220D ... 275D | 345Y...415Y 380Y...480Y | 12.5D 12.6D | 7.2Y 7.3Y | -340 -380 | 410 360 | 72 74 | 40 40 |
| A 242 | 2MV 520-H57 | 50 | 4.0 | 345D ... 415D 380D ... 480D | 600Y...720Y 600Y...720Y | 10.0D 9.9D | 5.8Y 5.71Y | -390 -410 | 440 480 | 72 74 | 44 44 |
| A 243 | 2MV 520-H57 | 60 | 4.6 | | | | | | | | |



Other voltage ranges

| 2MV520 | | |
|---|---|-------------------|
| 50Hz | 60Hz | |
| 3~ | | ↑ ↑ |
| 185...225 V D/320...390 V Y 200...240 V D/345...415 V Y 345...415 V D | 200...240 V D/345...415 V Y 200...275 V D/380...480 V Y 380...480 V D | H 1 H 6 H 7 |
| 500 V D | 575 V D | C 5 |

Further voltage range on request; please quote in plain text.

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given do not constitute an obligation from our side to deliver as shown.



XT Dongguan HongGuang Hardwares Co., Ltd.

Add: C712 Mingzhi Building, Nancheng District, Dongguan, Guangdong, China. 523000

Cell/whatsapp: +86-137-1292-7830 Tel: +86-769-28639650

Website: www.manvac.cn www.manvacblowers.com